



Dadi autoaggancianti filettati

M	Tipo	Sm	D ^{+0.2} _{-0.2}	D1 _{max.}	H ^{+0.2} _{-0.2}	H1 _{max.}	F ^{+0.08} _{-0.0}	Dm
M4x0,7	0	0,8	7,9	5,38	2,0	0,77	5,4	6,9
	1	1,0				0,97		
	2	1,4				1,38		
	3	2,3				2,20		
M5x0,8	0	0,8	8,7	6,38	2,0	0,77	6,4	7,1
	1	1,0				0,97		
	2	1,4				1,38		
	3	2,3				2,20		
M6x1,0	1	1,4	11,05	8,72	4,08	1,38	8,75	8,6
	2	2,3				2,20		
	3	3,2				3,0		
M8x1,25	1	1,4	12,65	10,47	5,47	1,38	10,5	9,7
	2	2,3				2,20		
	3	3,2				3,0		
M10x1,5	1	2,3	14,3	12,65	6,72	2,20	12,7	11
	2	3,2				3,0		
M10x1,5	1	2,3	17,35	13,9	7,5	2,20	14,0	11
	2	3,2				3,0		

F = Foratura

Dm = Distanza minima dal bordo

Sm = Spessore minimo lamiera